



SECTION VIEW A-A

SPECIFICATIONS	
UNITS:	IN (mm)
LOAD RATINGS	C: 4,300 LBS Co: 2,500 LBS
SPEED RATING	5300 RPM
GREASE TYPE	NLGI #2
GREASE FILL	40%
OPERATING TEMP	10°F - 200°F
SEAL TYPE	B-TYPE
INTERNAL CLEARANCE	C3
TORQUE SETTING ON SET SCREWS	

SOLVE INDUSTRIAL MOTION GROUP
PTI
 DWG. NO.

WEIGHT	2.76 LBS
MATERIAL	SEE BOM
COATING	SEE BOM
DRAWN	SEC 01/10/2025
CHECKED	SEC 01/10/2025
APPROVED	
THIRD ANGLE PROJECTION	
<small>PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLVE I.M.G. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLVE I.M.G. IS PROHIBITED.</small>	

3	M6 ZERK	STEEL	ZINC PLATED	1
2	HC206-19	BEARING STEEL	N/A	1
1	F206	CAST IRON	POWDER COAT	1
ITEM NO.	PART NUMBER	MATERIAL	COATING	QTY.
DATE BY REVISION DESCRIPTION REV				
ITEM DESCRIPTION: HCF206-19 SCALE 1:11				
REV -				