



SECTION VIEW A-A

3	M6 ZERK	STAINLESS STEEL	N/A	1
2	SHC208-40MM	STAINLESS STEEL	N/A	1
1	SFL208	STAINLESS STEEL	N/A	1
ITEM NO.	PART NUMBER	MATERIAL	COATING	QTY.

SPECIFICATIONS	
UNITS:	IN (mm)
LOAD RATINGS	C: 5,600 LBS Co: 3,200 LBS
SPEED RATING	4000 RPM
GREASE TYPE	FM222
GREASE FILL	40%
OPERATING TEMP	-10°F - 250°F
SEAL TYPE	K-TYPE
INTERNAL CLEARANCE	C3
TORQUE SETTING ON SET SCREWS	



WEIGHT	3.73 LBS
MATERIAL	SEE BOM
COATING	SEE BOM
DRAWN	SEC 01/14/2025
CHECKED	SEC 01/14/2025
APPROVED	
THIRD ANGLE PROJECTION	

DATE	BY	REVISION DESCRIPTION	REV
ITEM DESCRIPTION: SHCSFL208-40MM			SCALE 1:9
			REV -

DWG. NO. PROPRIETARY AND CONFIDENTIAL  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLVE IMG. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLVE IMG IS PROHIBITED.