



SECTION VIEW A-A

3	M6 ZERK	STAINLESS STEEL	N/A	1
2	SUC208-40MM	STAINLESS STEEL	N/A	1
1	SPA208	STAINLESS STEEL	N/A	1
ITEM NO.	PART NUMBER	MATERIAL	COATING	QTY.

SPECIFICATIONS		SOLVE		WEIGHT	
UNITS:	IN (mm)	INDUSTRIAL MOTION GROUP		4.54 LBS	
LOAD RATINGS	C: 5,600 LBS Co: 3,200 LBS			MATERIAL	SEE BOM
SPEED RATING	4000 RPM	COATING	SEE BOM	DRAWN	SEC 01/02/2025
GREASE TYPE	FM222	CHECKED	FP 01/08/2025	APPROVED	
GREASE FILL	40%				
OPERATING TEMP	-10°F - 250°F				
SEAL TYPE	K-TYPE				
INTERNAL CLEARANCE	C3				
TORQUE SETTING ON SET SCREWS		SIZE	B	DWG. NO.	PTI

DATE	BY	REVISION DESCRIPTION	REV
ITEM DESCRIPTION:			SCALE
SUCSPA208-40MM			1:10
			REV
			-

9 8 7 6 5 4 3 2 1

9 8 7 6 5 4 3 2 1

G
F
E
D
C
B
A

G
F
E
D
C
B
A