



SECTION VIEW A-A

ITEM NO.	PART NUMBER	MATERIAL	COATING	QTY.
3	M6 ZERK	STAINLESS STEEL	N/A	1
2	UCX10-31	BEARING STEEL	N/A	1
1	FX10	STAINLESS STEEL	POWDER COAT	1

SPECIFICATIONS		WEIGHT	
UNITS:	IN (mm)		8.02 LBS
LOAD RATINGS	C: 9,700 LBS Co: 6,600 LBS	MATERIAL	SEE BOM
SPEED RATING	3100 RPM	COATING	SEE BOM
GREASE TYPE	NLGI #2	DRAWN	SEC 01/03/2025
GREASE FILL	40%	CHECKED	KODS 01/06/2025
OPERATING TEMP	10°F - 200°F	APPROVED	
SEAL TYPE	B-TYPE	THIRD ANGLE PROJECTION	
INTERNAL CLEARANCE	C3		
TORQUE SETTING ON SET SCREWS			



PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLVE IMG. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLVE IMG IS PROHIBITED.

DATE	BY	REVISION DESCRIPTION	REV
		ITEM DESCRIPTION: UCFX10-31	SCALE 1:7
			REV -