





9
8
7
6
5
4
3
2
1

G
F
E
D
C
B
A

SECTION VIEW A-A

SPECIFICATIONS		SOLVE 		WEIGHT		1.33 LBS	
UNITS:	IN [mm]	MATERIAL		SEE BOM			
LOAD RATINGS	C: 2,900 LBS Co: 2,500 LBS	COATING		SEE BOM			
SPEED RATING	7450 RPM	DRAWN		SEC	01/02/2025		
GREASE TYPE	NLGI #2	CHECKED		FP	01/08/2025		
GREASE FILL	40%	APPROVED					
OPERATING TEMP	10°F - 200°F	THIRD ANGLE PROJECTION					
SEAL TYPE	B-TYPE	DWG. NO.		PROPRIETARY AND CONFIDENTIAL			
INTERNAL CLEARANCE	C3			THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLVE IMG. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLVE IMG IS PROHIBITED.			
TORQUE SETTING ON SET SCREWS							

3	M6 ZERK	STEEL	ZINC PLATED	1
2	UC204-12	BEARING STEEL	N/A	1
1	PA204	CAST IRON	POWDER COAT	1
ITEM NO.	PART NUMBER	MATERIAL	COATING	QTY.