



| SPECIFICATIONS | | WEIGHT | |
|------------------------------|-------------------------------|------------------------|----------------|
| UNITS: | IN [mm] | | 9.20 LBS |
| LOAD RATINGS | C: 9,780 LBS Co: 6,580 LBS | MATERIAL | SEE BOM |
| SPEED RATING | 3100 RPM | COATING | SEE BOM |
| GREASE TYPE | NLGI #2 | DRAWN | SEC 12/26/2024 |
| GREASE FILL | 40% | CHECKED | SEC 01/07/2025 |
| OPERATING TEMP | 10°F - 200°F | APPROVED | |
| SEAL TYPE | B-TYPE | THIRD ANGLE PROJECTION | |
| INTERNAL CLEARANCE | C3 | | |
| TORQUE SETTING ON SET SCREWS | | | |

| ITEM NO. | PART NUMBER | MATERIAL | COATING | QTY. |
|----------|-------------|---------------|-------------|------|
| 3 | M6 ZERK | STEEL | ZINC PLATED | 1 |
| 2 | HC211-35 | BEARING STEEL | N/A | 1 |
| 1 | WS211 | CAST IRON | POWDER COAT | 1 |

| DATE | BY | REVISION DESCRIPTION | REV |
|------|----|-----------------------------|-----------|
| | | ITEM DESCRIPTION: WS211-35A | SCALE 1:7 |
| | | | REV - |



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SOLVE IMG. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SOLVE IMG IS PROHIBITED.